

SUPINATION/PRONATION THERAPY DEVICE

The present invention relates to an orthotic device that promotes supination and pronation of a patient's wrist. A combination of components of the device allows it to apply either dynamic or static rotational forces to a joint in need of therapy. The force generated by the components and their direction can be quantified and used in therapeutic treatment.

Background of the Invention

There are many known orthotic devices including those specifically directed to rehabilitation of various joints such as elbows and wrists. Typically, these apparatuses are static or have a single pressure/force that is applied during operation. Those forces may be uneven across the device.

Another problem with existing devices is that none promote rotation or create rotational forces. It is common in wrist or arm injuries to have some temporary or permanent loss of rotation in the forearm/wrist, for instance when an arm is immobilized in a cast for an extended period of time. Whether there is a reduction in the range of supination or pronation, a patient can lose that flexibility of rotation. There are few known therapies to treat this loss of rotation. Typically, any rotational therapy is effectively limited to a therapist's office or similar rehabilitation facility.

Summary of the Invention

Accordingly, it is an object of the present invention to overcome the foregoing drawbacks and problems. The present invention provides a device that creates rotational forces to promote both supination or pronation of a wrist in need of therapy. The forces generated by the device are either dynamic or static. Preferably, the forces can be quantified and used in therapeutic treatment in accordance with treatment guidelines.

In one embodiment, an orthotic device for promoting supination and pronation includes a forearm enclosure adapted to substantially wrap around a forearm. A forearm support member is adapted to slidably receive the forearm enclosure wherein the support member wraps partially around the forearm enclosure. A post is mounted on the forearm enclosure. An anchor is mounted on the support member. A tensioning member is connected on one end to the anchor and on the other end to the post, wherein a rotational force of supination or pronation will be created on the forearm enclosure depending on the direction which the tensioning member is extended from the anchor to the post. The orthotic device may include a plurality of posts mounted at different locations on the forearm enclosure. The tensioning member may be comprised of an elastic material or inelastic material and may have an adjustable length. The orthotic device may further include an upper arm support member connected on one end to the forearm support member and adapted to substantially wrap around and support an upper arm. The upper arm support member may be hingedly

connected or fixedly connected to the forearm support member. The fixed connection from a forearm support member to a upper arm support member may be predetermined, and the predetermined angle may be substantially 90 degrees. The angle of connection of the upper arm support member and forearm support member may be variable.

In another embodiment, an orthotic device for promoting supination and pronation includes a forearm enclosure adapted to substantially wrap around a forearm. A forearm support member is adapted to slidably receive the forearm enclosure wherein the support member wraps partially around the forearm enclosure. Tensioning means have a first end and a second end. The orthotic device further includes means for attaching the tensioning means on the first end to the forearm enclosure and on the second end to the forearm support member. A rotational force of supination or pronation will be created on the forearm enclosure depending on the direction which the tensioning means is attached to the forearm support member and the forearm enclosure.

In a still further embodiment, a kit for assembling an orthotic device includes a forearm enclosure adapted to substantially wrap around a forearm. The kit further includes a forearm support member adapted to slidably receive the forearm enclosure wherein the support member is adapted to wrap partially around the forearm enclosure. A post is mountable on the forearm enclosure. An anchor is mountable on the

support member. And the kit further includes a tensioning member connectable on one end to the anchor and on the other end to the post.

Brief Description of the Drawings

Figure 1 is a perspective view of an orthotic device in accordance with the present invention.

Figure 2 is a partial, exploded perspective view of the orthotic device shown in Figure 1.

Figure 3 is an exploded view of the forearm enclosure portion of the orthotic device shown in Figure 1.

Figure 4 is a side elevation view of an orthotic device as shown in Figure 1.

Figure 5 is an alternative embodiment of an orthotic device in accordance with the present invention.

Figure 6 is a side elevation, partially exploded view of the forearm enclosure portion of a preferred embodiment of the present invention.

Figures 7A and 7B are front elevation, cross-sectional views of a portion of the orthotic device in accordance with the present invention wherein the tensioning member is shown applying a rotational force in the counter clockwise direction(Figure 7A) and clockwise direction (Figure 7B).

Detailed Description of Preferred Embodiments

The present invention is directed to an orthotic device used to promote the rotation of a patient's wrist and forearm. The rotation of the wrist in the direction in which the palm is pointed upwardly or skywardly is called supination. The rotation of the wrist in which the palm is facing downwardly is referred to as pronation. The orthotic device described herein can apply either a dynamic or static force in the rotational direction of supination or pronation. Further, that rotational force may be varied by a user or therapist in accordance with the needs of a patient.

Turning now to the drawings, Figure 1,2 and 4 illustrate an orthotic device in accordance with the present invention in which a dynamic force of rotation can be applied to a patient's forearm. (There is reference made throughout of a patient's "wrist" or "forearm" when referring to the application of therapy herein. The terms are effectively referenced to interchangeably.) The orthotic device 10 is a brace adapted to support a patient's upper arm and forearm. The device 10 is made up of a forearm support member 11 and an upper arm support member 12 that are hingedly connected about a hinge 20. A forearm enclosure 13 is adapted to receive and substantially wrap around a patient's forearm. The forearm enclosure 13 is slidably received within the forearm support member 11.

The upper arm support member 12 has two straps 17 that connect the sides of the support member about a patient's arm 14. The straps 17 are made of strips of hook and loop fasteners (VELCRO straps) that loop

through rings 16 that are connected by screws 15 to the upper arm support member 12. In this way, the particular size of a patient's arm 14 and the tightness of fit can be accommodated by varying the length of the strap 17.

The hinge 20 attaches the lower end of the upper arm support member 12 to the upper end of the forearm support member 11. The hinge 20 is locked in the substantially 90° relative position (forearm support member to upper arm support member) by a pin 22 releaseably screwed into one of a number of apertures 21. As can be seen, there are a number of apertures 21 thereby allowing the device 10 to have a variable angle defined by the forearm support member 11 and upper arm support member 12. A therapist or patient can predetermine the specific angle that is desirable for a given patient. Of course, the device 10 could have a predetermined, single angle that is nonadjustable. A problem is that many times patients in need of rotational wrist therapy will have other arm injuries that limit the flexion and extension of a patient's arm. Sometimes it is not possible or desirable to have the 90° angle. From a simple supination/pronation therapy standpoint, it is preferred to have the angle of the upper arm relative to the forearm at substantially 90°. In this way, the supination/pronation rotation will be focused on the bones, tendons and muscles in the forearm (wrist) rather than in potential compensating motion of other parts of a patient's arm.

The forearm support member 11 is adapted to receive a forearm enclosure 13 that is wrapped around a forearm. The support member 11

includes a strap 17 that extends from one side of the support member to the other in order to retain the support member attached to a patient's forearm. This strap 17 on the forearm support member 11 is not necessary, but it helps to stabilize the complete device 11. The forearm support member 11 also has rings 46 and screws 45 fastened on either side of the support member. These rings 46 and screws 45 are anchors onto which may be attached straps 40. The straps 40 are part of a tensioning member that includes elastic band 41 that is attached to those straps by clamps 42.

The forearm enclosure 13 is adapted to encircle most of a patient's forearm. The forearm enclosure 13 is preferably molded or fitted to create a snug fit on the forearm. A typical forearm enclosure could be some kind of cast. Other enclosure devices are possible. It is the forearm enclosure 13 that is rotated by the present device, so it must fit tightly enough about the forearm (wrist) to cause the rotation that promotes supination and pronation. In order to make the forearm enclosure 13 fit more comfortably and snugly about a wrist, padding 31 is used to line the inside of the forearm enclosure. The forearm enclosure 13 also includes holes 36. Mounted in the holes 36 are posts 35. The posts 35 are adapted to protrude a small distance from the forearm enclosure 13 yet be securely fitted to it. The forearm enclosure 13 is preferably made of a relatively stiff material. For instance, when a forearm enclosure is a cast, acceptable cast materials include, preferably, Kydex. This can be the same plastic material as the material that makes up the forearm support member 11 and the upper

support arm member 12. The forearm enclosure and support member may be fabricated from virtually any material that meets the functional requirements described herein. The plastic material is preferred for its light weight and inexpensive cost. It is essential that the forearm enclosure 13 be able to slide easily over the surface of the inside of the forearm support member 11. This allows for the rotation of the forearm enclosure 13 with minimal drag.

In operation, straps 40 are looped through rings 46 that are in the forearm support member. The straps are then wrapped in a clockwise or counter clockwise direction around the forearm support member 11, and the elastic band 41 is looped over one or more of the posts 35. This creates a dynamic force of rotation in the given direction. By looping the elastic band 41 over more than one post 35, a greater rotational force is created. Also, as can be seen, the posts 35 can be moved to other holes 36 to thereby lessen or increase the amount of rotation and rotational force applied to the forearm inside the forearm enclosure 13. The rotation of the forearm enclosure 13 in the clockwise or counter clockwise direction is best seen in Figures 7A and 7B.

In the figures shown, the anchors that are made up of the rings 46 and the bolts 45 are positioned on both sides of forearm support member 11. It is possible to mount any type of anchor in one place, for instance on the bottom of the forearm support member 11, that allows the straps to be easily wrapped in the clockwise or counter clockwise direction. The side

mounting of the anchors is a matter of choice to make the bottom of the forearm support member 11 relatively flat.

Referring now specifically to Figures 3 and 6, the forearm enclosure 13 can be more specifically discussed. The forearm enclosure 13 is adapted to engage a patient's forearm and wrist. Strap 30 wraps around the end of the forearm enclosure to secure the end of the forearm enclosure 13 about a patient's hand and wrist. Padding 31 can be used to line the forearm enclosure 13. The padding 31 is connected to the inside of the forearm enclosure 13 by way of patches of hook and loop fasteners 38. The padding 31 is preferably not permanently glued inside the forearm enclosure 13. In this way, the screws 37 that are attached to the posts 35 may be removed and placed in alternative holes 36 or 39 in the forearm enclosure 13. In lieu of the holes 36 and 39 that are predrilled into the forearm enclosure 13, slots (that are not shown) may be used. In this way, the exact position about the perimeter of the forearm enclosure 13 may be selected for the posts 35. Similarly, other types of posts or means of receiving a tensioning member may be used to connect the forearm enclosure to the tensioning member 41.

Figure 5 illustrates an alternative embodiment of the invention in which a static force of rotation is applied to the forearm enclosure 13. The anchors made up of the bolts 45 and rings 46 are the same anchors as used in connection with the dynamic embodiment described earlier. The tensioning member or straps 50 have a fixed a length that is made of hook

and loop fastener (VELCO®) material. The straps 50 are inelastic, and therefore apply no dynamic force on the cast 13. The straps 50 have apertures 51 that loop over the posts 35. The result is that once a strap 50 is attached at one end to a ring 46 and the other end to a post 35, a static rotational force is therefore created on the forearm enclosure 13. These retaining straps 50 may be used alone or together with the dynamic force of the elastic member 41 described earlier.

Many therapeutic scenarios are possible. These include the use of both static and dynamic straps. For instance, a patient could use an elastic member to apply a dynamic force of rotation on a cast for only a part of the day. Other times, the patient could attach the static strap to the wrist in order to maintain a range of motion or to prevent a painful range of motion. Alternatively, both static and dynamic straps could be attached to a post in opposing directions. This could be used to limit rotation in the direction of the dynamic force up to a certain amount. In this way, incremental rotational force is obtained. This also prevents over rotation as a result of a dynamic force. Finally, a patient could use two static straps wrapped around the device in opposite directions in order to set boundaries of rotation of a wrist of a patient. In other words, the static straps would allow a predetermined number of degrees of rotation and could prevent painful or dangerous over rotation by a patient.

The dynamic force of rotation may be adjustable in many different ways in accordance with the present invention. First, the user could change

the length of the static straps 40 which are attached to an elastic cord 41. Second, the length of the elastic cord 41 can be varied. Third, the number of posts 35 around which the elastic cord 41 is looped may be varied. Fourth, the elasticity of the cord 41 may be varied. In some therapy, it may be desirable to quantify the treatment. In those cases, a gauge may be used on a post or anchor, or in a strap, to determine the specific amount of rotational force being applied to the cast.

As shown, the device is a brace that is wrapped around both the upper arm and forearm of a patient. This is preferred, because it keeps the forearm support member stable and does not allow it to rotate around a forearm. If the device was a forearm support only, then the support member could rotate around a forearm, thereby removing any rotational force on the wrist (forearm enclosure) of the user. It is preferred that there is at least some support above the elbow that this used to stabilize the forearm support member and not allow the shoulder to accommodate for a lack of rotation.

The device described herein is intended to be simple to use and available to any patient or therapist. Therefore, it is envisioned that a kit containing the components described herein will be available to users or to therapists. Since some of the components will vary in size depending on a given patient, a therapist will be able to easily assemble the parts of the kit to meet individual needs.

While the invention has been described with reference to specific embodiments thereof, it will be understood that numerous variations, modifications and additional embodiments are possible, and accordingly, all such variations, modifications, and embodiments are to be regarded as being within the spirit and scope of the invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2